

task_ddjurcpk494go2q1_with_calculation

Student Group

First Name	Surname	Matrikel Nr.

Table of Contents

Exercise E1 Capacitor (written test, approx. 12 % of a 120-minute written test, SS2024) 2

qq

electric field, magnetic field, exam ee2 SS2024

Exercise E1 Capacitor

(written test, approx. 12 % of a 120-minute written test, SS2024)

2. With the graph of the magnitude of the electric field strength E of a parallel plate capacitor, the diagram shows the cross-section of the capacitor. The inner conductor has a diameter of 0.6 mm and the outer conductor has a diameter of 1.2 mm . The inner conductor is connected to the positive terminal of a DC voltage source and the outer conductor is connected to the negative terminal. The diagram shows the cross-section of the capacitor with the inner conductor on the left and the outer conductor on the right. The inner conductor has a diameter of 0.6 mm and the outer conductor has a diameter of 1.2 mm . The inner conductor is connected to the positive terminal of a DC voltage source and the outer conductor is connected to the negative terminal. The diagram shows the cross-section of the capacitor with the inner conductor on the left and the outer conductor on the right. The inner conductor has a diameter of 0.6 mm and the outer conductor has a diameter of 1.2 mm . The inner conductor is connected to the positive terminal of a DC voltage source and the outer conductor is connected to the negative terminal.

Path

- Inner conductor: $+3.3 \text{ mA}$, $+10 \text{ nC}$ (current into the plane of the diagram)
- for $(0.1 \text{ mm} | 0)$: $E_{\text{in}} = 5.28 \text{ V/m}$
- Outer conductor: -3.3 mA , 0 nC (current out of the plane of diagram)
- for $(0.55 \text{ mm} | 0)$: $E_{\text{out}} = 6.985 \text{ V/m}$

The magnitude of the electric displacement field D can be calculated by: $\int D \cdot dA = Q_{\text{enc}}$.

In general, the D -field is proportional to $\frac{1}{r}$ for the situation between both conductors.

For the D -field on the surface of the inner conductor, we get $D = \frac{Q}{2\pi r l}$ with $Q = C \cdot U$.

This is proportional to the area within this radius. Therefore, the formula $H = \frac{I}{2\pi r}$ gets $H_{\text{in}} = \frac{I}{2\pi (0.1 \text{ mm})}$ and $H_{\text{out}} = \frac{I}{2\pi (0.55 \text{ mm})}$.

So, we get for $D_{\text{in}} = \frac{Q}{2\pi (0.1 \text{ mm})}$ and $D_{\text{out}} = \frac{Q}{2\pi (0.55 \text{ mm})}$. This leads to a formula proportional to $\frac{1}{r}$.

For x within the outer conductor one also gets a linear proportionality with $D_{\text{out}} = \frac{Q}{2\pi (0.55 \text{ mm})}$ and $D_{\text{in}} = \frac{Q}{2\pi (0.1 \text{ mm})}$.

Hint: For the direction, one has to consider the sign of the enclosed charge. By this, we see that the D -field is positive.

But here, again only the magnitude was questioned!

.. What is the magnitude of the magnetic field strength H at $(0.1 \text{ mm} | 0)$ and $(0.55 \text{ mm} | 0)$?

Path

The magnitude of the magnetic field strength H can be calculated by: $H = \frac{I}{2 \pi \cdot r}$

So, we get for H_{i} at $(0.1 \text{ mm} \mid 0)$, and H_{o} at $(0.55 \text{ mm} \mid 0)$:

$$\begin{aligned} H_{\text{i}} &= \frac{I}{2 \pi \cdot r_{\text{i}}} \quad \&= \frac{+3.3 \text{ A}}{2 \pi \cdot \{0.1 \cdot 10^{-3} \text{ m}\}} \quad \& H_{\text{o}} &= \frac{I}{2 \pi \cdot r_{\text{o}}} \\ & &= \frac{+3.3 \text{ A}}{2 \pi \cdot \{0.55 \cdot 10^{-3} \text{ m}\}} \quad \end{aligned}$$

Hint: For the direction, one has to consider the right-hand rule. By this, we see that the H -field on the right side points downwards.

Therefore, the sign of the H -field is negative.

But here, only the magnitude was questioned!

From:

<https://wiki.mexle.org/> - **MEXLE Wiki**

Permanent link:

https://wiki.mexle.org/ee2/task_ddjurcpk494go2q1_with_calculation?rev=1721069601

Last update: **2024/07/15 20:53**

