

# task\_ddjurcpk494go2q1\_with\_calculation

## Student Group

First Name	Surname	Matrikel Nr.

## Table of Contents

Exercise E1 Fields of an coax Cable (written test, approx. 12 % of a 120-minute written test, SS2024) ..... 2

electric field, magnetic field, exam ee2 SS2024

Exercise E1 Fields of an coax Cable (written test, approx. 12 % of a 120-minute written test, SS2024)

2. Plot the graph of the magnitude of the electric field  $E(r)$  with  $r$  in  $\text{mm}$ . The dia  $d = 0.6 \text{ mm}$  shows the cross-section of the inner conductor with  $(0.6 \text{ mm} | 0)$  in center. The diagram also depicts dimensions and labels for the diagram that appears:

Path

Inner conductor:  $+3.3 \text{ mA}$ ,  $+10 \text{ nC}$  (current into the plane of the diagram)

Outer conductor:  $-3.3 \text{ mA}$ ,  $0 \text{ nC}$  (current out of the plane of diagram)

- for  $(0.1 \text{ mm} | 0)$ :  $E_{\text{in}} = 3.28 \dots \text{ V/m}$
- for  $(0.55 \text{ mm} | 0)$ :  $E_{\text{out}} = 0.985 \dots \text{ V/m}$

The magnitude of the electric displacement field  $D$  can be calculated by:  $\int D \cdot dA = Q_{\text{enc}}$ .

In general, the  $E$ -field is proportional to  $\frac{1}{r}$  for the situation here, if the position radius of the enclosing area is the surface of a cylindrical shape (here for simplicity without the round endings).

For the  $E$ -field, a circle with the same center as the inner conductor is drawn through the conductor within a circle with the radius  $x$ .

This is proportional to the area within this radius. Therefore, the formula  $H = \frac{I}{2\pi r}$  gets  $H(x) = \frac{I_{\text{enc}}}{2\pi \cdot x}$ .

So, we get for  $D$  in  $\text{C/m}^2$  at  $r = 0.1 \text{ mm}$  and  $D$  in  $\text{C/m}^2$  at  $r = 0.55 \text{ mm}$ :

- For  $x$  within the inner conductor:  $D_{\text{in}} = \frac{Q_{\text{enc}}}{2\pi \cdot r_{\text{in}} \cdot l} = \frac{10 \cdot 10^{-9} \cdot C}{2\pi \cdot 0.1 \cdot 10^{-3} \cdot 0.5 \cdot 10^{-3}}$
- For  $x$  within the outer conductor:  $D_{\text{out}} = \frac{Q_{\text{enc}}}{2\pi \cdot r_{\text{out}} \cdot l} = \frac{10 \cdot 10^{-9} \cdot C}{2\pi \cdot 0.55 \cdot 10^{-3} \cdot 0.5 \cdot 10^{-3}}$

Hint: For the direction, one has to consider the sign of the enclosed charge. By this, we see that the  $D$ -field is positive. But here, again only the magnitude was questioned!

.. What is the magnitude of the magnetic field strength  $H$  at  $(0.1 \text{ mm} | 0)$  and  $(0.55 \text{ mm} | 0)$ ?

Path

The magnitude of the magnetic field strength  $H$  can be calculated by:  $H = \frac{I}{2 \pi \cdot r}$

So, we get for  $H_{\text{i}}$  at  $(0.1 \text{ mm} \mid 0)$ , and  $H_{\text{o}}$  at  $(0.55 \text{ mm} \mid 0)$ :

$$\begin{aligned} H_{\text{i}} &= \frac{I}{2 \pi \cdot r_{\text{i}}} \quad \&= \frac{+3.3 \text{ A}}{2 \pi \cdot \{0.1 \cdot 10^{-3} \text{ m}\}} \quad \& H_{\text{o}} &= \frac{I}{2 \pi \cdot r_{\text{o}}} \\ & &= \frac{+3.3 \text{ A}}{2 \pi \cdot \{0.55 \cdot 10^{-3} \text{ m}\}} \quad \end{aligned}$$

Hint: For the direction, one has to consider the right-hand rule. By this, we see that the  $H$ -field on the right side points downwards.

Therefore, the sign of the  $H$ -field is negative.

But here, only the magnitude was questioned!

From:

<https://wiki.mexle.org/> - MEXLE Wiki

Permanent link:

[https://wiki.mexle.org/electrical\\_engineering\\_and\\_electronics/task\\_ddjurcpk494go2q1\\_with\\_calculation?rev=1721072277](https://wiki.mexle.org/electrical_engineering_and_electronics/task_ddjurcpk494go2q1_with_calculation?rev=1721072277)

Last update: **2024/07/15 21:37**

